

In-Line GFCI Protected Quad Boxes

Box enclosed in heavy impact resistant polymer case. Spring loaded covers protect each pair of receptacles. "Fast Breaker" built in for convenient reset. GFCI with lighted indicator located at power end provides protection to the cord and tools attached. Applications include:

- ▶ Drills
- ▶ Saws
- ▶ Multiple Tools Use
- ▶ Lathes
- ▶ Lighting
- ▶ Construction Sites

Standard lengths: 6', 25', 50'. To prevent unmonitored equipment startup, manual reset is required after GFCI trip and power outage. Complies with National Electric Code (NEC 2008) Article 590.6 for "Temporary Installations".

FEATURES

- 26020-009**(6') ⓘ
- 26020-010**(25')
- 26020-004**(50')
- 25080-121**(2') ⓘ
- 25080-122**(6')
- 25080-123**(25')

- ▶ Volts/Amps: 120V/15A
- ▶ Cord Gauge: 12/3 AWG.
- ▶ NEMA 5-15P & (4)5-15R
- ▶ Trip Level: 4 - 6 mA
- ▶ Volts/Amps: 120V/20A
- ▶ Cord Gauge: 12/3 AWG.
- ▶ NEMA 5-20P & (4)5-20R
- ▶ Trip Level: 4 - 6 mA
- ▶ Available in 2', 6', 25'



TECHNICAL DATA

Grounded Neutral	4 Ohms typical
Trip response time for ground fault and grounded neutral trip	less than 25mS
Voltage surge withstand	3kv ringwave test and 4kv/2kA surge immunity test
Radio frequency noise susceptibility	operates within normal limits with 0.5 volts injected on power line 150kHz-230mHz
Frequency	50 / 60 Hz
Endurance	3,000 operations minimum
Overload Current	six times rated current
Operating temperature range	-35° C to 66° C
Effect of 10 Amp turn DC Shock on ground fault trip	5% maximum trip level variation
Insulation voltage	1500 VRMS - 1 Min.
Power On indication	lighted indicator



15 Amp version pictured

